

CFM Performance / Collar Size Information - Table 'J'
Hood Models FSR-I, FSP-I, FSP-A-I, EC-FP-I, EC-FR-I - Island Application

Hood Length	Number of Sections	Qty. of Collars Exh/Sup	LIGHT	COOKING	MEDIUM	COOKING	HEAVY	COOKING
			EXHAUST CFM & Collar Size(LxW)	SUPPLY CFM & Collar Size(LxW)	EXHAUST CFM & Collar Size(LxW)	SUPPLY CFM & Collar Size(LxW)	EXHAUST CFM & Collar Size(LxW)	SUPPLY CFM & Collar Size(LxW)
4'	2	1/2	1280 (1) 12 x 10	1150 (2)12 x 12	1680 (1) 12 x 12	1520 (2)12 x 12	2320 (1) 14 x 14	2090 (2)12 x 12
5'	2	1/2	1600 (1) 12 x 10	1440 (2)12 x 12	2100 (1) 14 x 14	1890 (2)12 x 12	2900 (1) 16 x 16	2610 (2)14 x 12
6'	2	1/2	1920 (1) 14 x 12	1730 (2)12 x 12	2520 (1) 16 x 14	2270 (2)12 x 12	3480 (1) 18 x 16	3130 (2)16 x 12
7'	2	1/2	2240 (1) 14 x 14	2020 (2)12 x 12	2940 (1) 16 x 16	2650 (2)14 x 12	4060 (1) 20 x 18	3660 (2)20 x 12
8'	2	1/2	2560 (1) 16 x 14	2310 (2)14 x 12	3360 (1) 18 x 16	3030 (2)16 x 12	4640 (1) 20 x 20	4180 (2)20 x 12
9'	2	1/2	2880 (1) 16 x 16	2590 (2)14 x 12	3780 (1) 18 x 18	3400 (2)18 x 12	5220 (1) 22 x 20	4700 (2)24 x 12
10'	2	1/2	3200 (1) 18 x 16	2880 (2)16 x 12	4200 (1) 20 x 18	3780 (2)20 x 12	5800 (1) 24 x 22	5220 (2)26 x 12
11'	2	1/2	3520 (1) 18 x 18	3170 (2)16 x 12	4620 (1) 20 x 20	4160 (2)22 x 12	6380 (1) 24 x 24	5744 (2)28 x 12
12'	2	1/2	3840 (1) 18 x 18	3460 (2)18 x 12	5040 (1) 22 x 20	4540 (2)24 x 12	6960 (1) 24 x 24	6270 (2)32 x 12
13'	2	2/4	4160 (2) 14 x 12	3740 (4)12 x 12	5460 (2) 16 x 14	4920 (4)14 x 12	7540 (2) 18 x 18	6790 (4)18 x 12
14'	2	2/4	4480 (2) 14 x 14	4030 (4)12 x 12	5880 (2) 16 x 16	5300 (4)14 x 12	8120 (2) 20 x 18	7310 (4)18 x 12
15'	4	2/4	4800 (2) 14 x 14	4320 (4)12 x 12	6300 (2) 18 x 16	5670 (4)16 x 12	8700 (2) 20 x 20	7830 (4)20 x 12
16'	4	2/4	5120 (2) 16 x 14	4610 (4)12 x 12	6720 (2) 18 x 16	6050 (4)16 x 12	9280 (2) 20 x 20	8350 (4)22 x 12
17'	4	2/4	5440 (2) 16 x 14	4900 (4)14 x 12	7140 (2) 18 x 18	6430 (4)18 x 12	9860 (2) 22 x 20	8880 (4)22 x 12
18'	4	2/4	5760 (2) 16 x 16	5190 (4)14 x 12	7560 (2) 18 x 18	6810 (4)18 x 12	10440 (2) 22 x 20	9400 (4)24 x 12
19'	4	2/4	6080 (2) 16 x 16	5480 (4)14 x 12	7980 (2) 20 x 18	7180 (4)18 x 12	11020 (2) 22 x 22	9920 (4)26 x 12
20'	4	2/4	6400 (2) 18 x	5760 (4)16 x 12	8400 (2) 20 x	7560 (4)20 x 12	11600 (2) 24 x	10440 (4)26 x 12

CFM Performance / Collar Size Information - Table 'J'
Hood Models FSR-I, FSP-I, FSP-A-I, EC-FP-I, EC-FR-I - Island Application

			16		18		22	
21'	4	2/4	6720 (2) 18 x 16	6050 (4)16 x 12	8820 (2) 20 x 20	7940 (4)20 x 12	12180 (2) 24 x 22	10965 (4)28 x 12
22'	4	2/4	7040 (2) 18 x 18	6340 (4)16 x 12	9240 (2) 20 x 20	8320 (4)22 x 12	12760 (2) 24 x 24	11490 (4)30 x 12
23'	4	2/4	7360 (2) 18 x 18	6630 (4)18 x 12	9660 (2) 22 x 20	8700 (4)24 x 12	13340 (2) 24 x 24	12010 (4)30 x 12
24'	4	2/4	7680 (2) 18 x 18	6910 (4)18 x 12	10080 (2) 22 x 20	9070 (4)24 x 12	13920 (2) 24 x 24	12530 (4)32 x 12